Questionnaire Fax-No.: +49 (0) 2841 6070 333



Steel running rails for roof serial no.					
Roof type	VP-UltraLine	VP-Lite	VP-Profi	VP-Classic	VP-Eco
Rail lock	laterally (left/right) (hole for connecting p	in laterally)		the bottom (piece for connecting pin	
with lock		•••		•	
without lock	► hole for connecting p	in at the botto	om		
/!	All part	iculars per	roof unit		/!
Front rail extens	ion 40 00 000 310 (left)	/ 40 00 000	320 (right) Fix	ed lengths	
$\begin{array}{c} & & \\ & & \\ \hline & & \\ \end{array} \begin{array}{c} & \\ & \\ \end{array} \end{array} $	L			L = 1172 mm L = 1745 mm L = 2710 mm gibbet pick-up dr	L = 1458 mm L = 2325 mm
hinged	plug-in type			adapter tube for	bracket VP-Classi
	000 330 (left) / 40 00 00		-		
	<u></u>		L1		
\oplus	· · · · · · · · · · · · · · · · · · ·		L2 L3		
	· · · · · · · ·	+	L3		
DB lock			L5		
End rail 40 00 000	0 350 / 40 00 000 360 (lei	ft & right)	L =		mm
ŀ	L		Y =	=	mm
	- φ φ φ φ φ φ φ φ φ φ φ φ φ φ φ φ φ φ φ	фф-	L 44 = 182	2 mm 🗌 C1	5 = 170 mm
$\left[\begin{array}{c} \bullet \end{array} \right]$	ф	···	LP = 155 n	nm 🗌 P1	5 = 141 mm
		Υ	P44 = 118		= 106,5 mm
DB lock	gi gi		PP = 91 m		_ = 392 mm
Surname:			Phone:		
First name:			Fax:		
Company name:			E-mail:		

© All rights are held by European Trailer Systems GmbH, including those for patent applications.

All powers of disposal, such as copying and dissemination rights, are held by us. Please note the copyright notice according to DIN ISO 16016!